

C-FL-B-RD Series

LED Bullet Light | Narrow, Medium and Wide Flood Light

Replaces up to 100W PSMH



A VERSATILE INSTALL

Our cULus Listed Bullet LED Flood Light features a 1/2-inch adjustable fitter mount and a narrow, medium or wide light distribution for precise aiming. It delivers either 2800 or 5000 lumens and is available in 4000K and 5000K.



C-FL-B-RDM-2L



C-FL-B-RDW-5L

PRODUCT SPECIFICATIONS

OVERVIEW

- Initial Delivered Lumens: 2800 Lumens (**2L**), 5000 Lumens (**5L**)
- CRI: ≥ 70
- CCT: Neutral White (4000K), Cool White (5000K)
- Input Power: 22W (**2L**), 40W (**5L**)
- Dimmable: Yes, 0-10V
- Distribution: Narrow (20°), Medium (40°) or Wide (75°)
- Operating Temperature Range: -40°F to 95°F (40°C to 35°C)
- Lifespan: Estimated > 50,000 Hours
- Power Factor: > 0.9
- Total Harmonic Distortion: < 20%
- Limited Warranty: 5-Year*
- Replaces 70W MH (**2L**), 100W PSMH (**5L**)

VERSATILE	RECOMMENDED USE	INPUT VOLTAGE
<ul style="list-style-type: none"> Come equipped with a threaded 1/2" NPT adjustable fitter mount for versatile install Narrow, medium or wide distribution Small, sleek design blends right into any application FCC Part 15, Subpart B, Class A limits for conducted and radiated emissions 	<ul style="list-style-type: none"> Building facades Landscape Signs & Monuments 	<ul style="list-style-type: none"> Universal (120V - 277V)

ORDERING INFORMATION

Example SKU: C-FL-B-RDN-2L-40K-DB

C-FL	B				DB
PRODUCT	SERIES	DISTRIBUTION	LUMENS	CCT	HOUSING COLOR
C-FL	B	RDN Narrow Distribution (20°) RDM Medium Distribution (40°) RDW Wide Distribution (75°)	2L 2800 Lumens 22W 5L 5000 Lumens 40W	40K Neutral White (4000K) 50K Cool White (5000K)	DB Dark Bronze

CERTIFICATIONS:




CA RESIDENTS WARNING: Cancer and Reproductive Harm - www.p65warnings.ca.gov

Rev. Date: V2.03/04/2022

For informational purposes only. Content is subject to change. *See creelighting.com/resources/warranties

C-FL-B-RD Series



SERIES OVERVIEW

DIMENSIONS	PRODUCT WEIGHT	MOUNTING HEIGHT	SPACING
6-5/8" D x 4-3/4" W x 6-7/8" H (2L) 7-1/2" D x 5-1/8" W x 7-3/8" H (5L)	1.78 lbs. (2L) 2.70 lbs. (5L)	Ground mounting	Space and aim as needed

FIXTURE SPECIFICATIONS

HOUSING	Heavy duty die-cast aluminum
LENS ASSEMBLY	Tempered glass lens
MOUNTING	Includes a 1/2" adjustable fitter, 6-inch wires coming out from the bottom of adjustable fitter

LUMINAIRE AND ELECTRICAL PERFORMANCE

OPERATING TEMPERATURE RANGE	ESTIMATED L ₇₀ LIFETIME @ 25°C (77°F)	POWER FACTOR	TOTAL HARMONIC DISTORTION
-40°F to -95°F (-40°C to 35°C)	>50,000 Hours	>0.9	<20%

SKU	DISTRIBUTION	COLOR TEMP	LUMEN OUTPUT	SYSTEM WATTS	CURRENT DRAW (AMPS)			
					120V	208V	240V	277V
C-FL-B-RDN-2L-40K-DB	Narrow Beam (20°)	4000K	2800 L	22W	0.187	0.113	0.102	0.094
C-FL-B-RDM-2L-40K-DB	Medium Beam (40°)							
C-FL-B-RDW-2L-40K-DB	Wide Beam (75°)							
C-FL-B-RDN-2L-50K-DB	Narrow Beam (20°)	5000K						
C-FL-B-RDM-2L-50K-DB	Medium Beam (40°)							
C-FL-B-RDW-2L-50K-DB	Wide Beam (75°)							
C-FL-B-RDN-5L-40K-DB	Narrow Beam (20°)	4000K	5000 L	40W	0.333	0.191	0.166	0.147
C-FL-B-RDM-5L-40K-DB	Medium Beam (40°)							
C-FL-B-RDW-5L-40K-DB	Wide Beam (75°)							
C-FL-B-RDN-5L-50K-DB	Narrow Beam (20°)	5000K						
C-FL-B-RDM-5L-50K-DB	Medium Beam (40°)							
C-FL-B-RDW-5L-50K-DB	Wide Beam (75°)							


* For more information on the IES BUG (Backlight-Uplight-Glare) Rating visit: <https://www.ies.org/wp-content/uploads/2017/03/TM-15-11BUGRatingsAddendum.pdf>. Valid with no tilt.

C-FL-B-RD Series

ISO PLOT CHART


C-FL-B-RDN-2L-40K

Mounting Height: 15'
Fixture Tilt: 60°




C-FL-B-RDN-5L-40K

Mounting Height: 20'
Fixture Tilt: 60°




C-FL-B-RDM-2L-40K

Mounting Height: 15'
Fixture Tilt: 60°



C-FL-B-RDM-5L-40K

Mounting Height: 20'
Fixture Tilt: 60°




C-FL-B-RD Series

ISO PLOT CHART


C-FL-B-RDW-2L-40K

Mounting Height: 15'
Fixture Tilt: 60°



C-FL-B-RDW-5L-40K

Mounting Height: 20'
Fixture Tilt: 60°



Note: All published photometric testing performed to IES LM-79-08 standards. Fixture photometry was completed on a single representative fixture. Foot candle levels are noted inside graph.

WARRANTY AND CERTIFICATIONS

WARRANTY	cULus LISTED	DLC
5-Year Limited*	Wet Location	Premium, 5.1

ACCESSORIES



Dark bronze 4-inch Round Weatherproof J-Box Cover with 1/2 inch NPT Threaded Knockout

SKU: E-ACC-MP4-DB

Use: For use with the 1/2-inch adjustable fitter mounts.

Dimensions: 4-1/2" D x 7/8" H

Construction: Dark bronze, powder coated diecast aluminum housing



White 4-inch Round Weatherproof J-Box Cover with 1/2 inch NPT Threaded Knockout

SKU: E-ACC-MP4-WH

Use: For use with the 1/2-inch adjustable fitter mounts.

Dimensions: 4-1/2" D x 7/8" H

Construction: White, powder coated die-cast aluminum housing

© 2022 Cree Lighting. A company of IDEAL INDUSTRIES. All rights reserved. For informational purposes only. Content is subject to change. Patent www.creelighting.com/patents. C-Lite and the C-Lite logo are registered trademarks of Cree Lighting. The cULus logo is a registered trademark of UL LLC. The DLC QPL logo and the DLC QPL Premium logo are registered trademarks of Northeast Efficiency Partnerships, Inc.

US: creelighting.com, e-conolight.com

Distribution/Sales: 855-617-2733 Customer Service: 888-243-9445

Rev. Date: V2 03/04/2022

For informational purposes only. Content is subject to change. *See creelighting.com/resources/warranties

C-LITE
LED LIGHTING