

C-WM-A-MWP Series

LED Wall Mount / Mini LED Wall Pack | Field Selectable CCT
Replaces 100W PSMH



THE PERFECT COLOR TEMPERATURE EVERY TIME

This Mini LED Wall Pack is a versatile lighting solution designed to meet your specific needs. With its CCT Selectable feature, you can easily adjust the color temperature to achieve the perfect lighting ambiance for any outdoor application. The included photocell ensures energy savings by automatically turning off the fixture during daylight hours. If desired, you can bypass or disable the photocell using the convenient on/off switch. It also features a frosted lens, providing comfortable illumination and reducing glare. Whether you prefer a j-box installation or a non-j-box installation, our Mini LED Wall Pack offers hassle-free setup for any space. UL Listed and includes a 3-year limited warranty.



PRODUCT SPECIFICATIONS

OVERVIEW

- Initial Delivered Lumens: up to 3600 Lumens
- CRI: ≥ 80
- Field selectable CCT options: 3000K (3125 Lumens), 4000K (3600 Lumens) or 5000K (3400 Lumens)
- Mounting height: 0-15 feet
- Input Power: 24W
- Dimmable: 0-10v dimming with dimming leads available for use in the field.
- Operating Temperature Range: -40°F to 104°F (-40°C to 40°C)
- Estimated L₇₀ Lifetime @ 25°C: > 100,000 hours
- Power Factor: > 0.9 at full load
- Total Harmonic Distortion: < 20% at full load
- Limited Warranty: 3 Years*
- Replaces 100W PSMH
- cULus Listed

FEATURES	RECOMMENDED USE	INPUT VOLTAGE
<ul style="list-style-type: none"> • Color temperature tunable for the perfect color light for your application • Photocell for easy energy savings, light will automatically go off during the day • On/Off switch for photocell if you want to bypass/disable the photocell • Frosted lens for comfortable glare reducing optical distribution • Easy install with or without a j-box • FCC Part 15, Subpart B, Class A limits for conducted and radiated emissions 	<ul style="list-style-type: none"> • Commercial • Entryways • General purpose • Security • Residential 	<ul style="list-style-type: none"> • Universal (120V through 277V Operation)

ORDERING INFORMATION

Example SKU: C-WM-A-MWP-3L-SCCT-UL-BZ

C-WM	A	MWP	3L	SCCT	UL	BZ
PRODUCT	SERIES	STYLE	LUMEN PACKAGE	FIELD SELECTABLE CCT	VOLTAGE	HOUSING COLOR
C-WM	A	MWP Mini Wall Pack	3L 3600 (24W)	SCCT Warm White (3000K) Neutral White (4000K*) Cool White (5000K)	UL Universal 120V through 277V operation	BZ Bronze

*Factory settings are set to 4000K.

CERTIFICATIONS:



C-WM-A-MWP Series

SERIES OVERVIEW

DIMENSIONS	PRODUCT WEIGHT	MOUNTING HEIGHT
8-1/2" L x 6-3/4" W x 3" D	1.56 lbs.	0-15 feet

FIXTURE SPECIFICATIONS

HOUSING	Bronze, high impact resistant, polycarbonate housing with diffused frosted lens for glare reduction
LENS ASSEMBLY	High impact polycarbonate diffused lens
MOUNTING	Will mount to either a j-box or can be mounted using surface conduit

ELECTRICAL PERFORMANCE

OPERATING TEMPERATURE RANGE	ESTIMATED L ₇₀ LIFETIME @ 25°C (77°F)	POWER FACTOR	TOTAL HARMONIC DISTORTION
-40°F to 104°F (-40°C to 40°C)	>100,000 Hours	> 0.9 at full load	< 20% at full load

SKU	REPLACES	INITIAL DELIVERED LUMENS			BUG RATINGS* (ALL CCTS)	SYSTEM WATTS	CURRENT DRAW (AMPS)			
		3000K	4000K	5000K			120V	208V	240V	277V
C-WM-A-MWP-3L-SCGT-UL-BZ	100W PSMH	3125	3600	3400	B1-U3-G2	24W	0.196A	0.113A	0.098A	0.085A

* For more information on the IES BUG (Backlight-Uplight-Glare) Rating visit: <https://www.ies.org/wp-content/uploads/2017/03/TM-15-11BUGRatingsAddendum.pdf>. Valid with no tilt.

WARRANTY AND CERTIFICATIONS

WARRANTY	cULus LISTED	DLC	DIMMABLE
3 Year Limited*	Wet Locations	—	0-10v dimming with dimming leads available for use in the field

 **CA RESIDENTS WARNING:** Cancer and Reproductive Harm – www.p65warnings.ca.gov

© 2025 Cree Lighting, A company of IDEAL INDUSTRIES. All rights reserved. For informational purposes only. Content is subject to change. Patent www.creelighting.com/patents. C-Lite and the C-Lite logo are registered trademarks of Cree Lighting. Due to continuous product improvement, information in this document is subject to change. The cULus logo is a registered trademark of UL LLC.

US: creelighting.com, e-conolight.com Distribution/Sales: 855-617-2733 Customer Service: 888-243-9445

Rev. Date: 02/06/2025

For informational purposes only. Content is subject to change. *See lighting.cree.com/warranty for details

C-LITE
LED LIGHTING